

VIVA combo™

RF Generator System



Global representative 

Bldg.C 4F, 158 Haneulmaeul-ro, ilsandong-gu, Goyang-si, Gyeonggi-do, Korea 10355
E: contact@stent.net T: +82 31 904 6153 F: +82 31 904 6157

Manufacturer 

Bldg.B 4F, 158 Haneulmaeul-ro, ilsandong-gu, Goyang-si, Gyeonggi-do, Korea 10355
E: info@STARmed4u.com T: +70 4673 8614 F: +82 0506 816 4546

www.taewoongmedical.com

TaeWoong
MEDICAL 

Solutions for Thermo-Ablation with RF medical technologies


- Temperature Mode for ELRA™

This mode is a temperature controlled system. It is applied to the generator with a pre-setting value (Temperature, Power, and Time) before procedures. Automatically, it begins to operate at a specific temperature, power output, and time duration

- Continuance Mode for EUSRA™

The RF power output is generated continuously with the setting value until the impedance value reaches 800 ohms

Under Continuance Mode, EUSRA™ has to connect with **VIVA PUMP** for cooling inside of the needle



VIVA PUMP

Internal cooling system - The VIVA PUMP circulates saline through the electrode to lower the temperature around the active tip of the electrode, inducing larger volumes of tissue and eliminating tissue charring



User Interface Description	
No.	Feature name
1	OHM/RESET button
2	MODE selection button
3	Part for indicating the operation status
4	RF START/STOP button
5	RF POWER control dial
6	RF CABLE connector
7	GROUND PADS connectors
8	Temperature display
9	TIME display
10	Impedance display
11	Watt display

Specification

- RF Power: 0~200watt @ 50 ohm load
- Operating frequency: 480KHz
- Temperature monitor: 5 °C - 95 °C
- Impedance monitor: 10~800 ohms